

D213 GP PRO

DUNLOP RECOMMENDED PRESSURES (BAR)				
		Setting Pressure		
Type	Target Running Pressure *	Cold (Ambient)	Tyre warmers (80°C) ****	Minimum running pressure ***
D213 GP PRO Front	2.6~2.8	2.3	2.6	2.4
D213 GP PRO Rear **	1.4~1.7	1.2	1.4	1.3

F/R	Size	Rim	Overall Diameter	Overall Width	Compound	L/S	SAP
			Inflated Dimensions				
F	120/70 ZR 17	17	601	116.5	MS1	58W	635913
F	120/70 ZR 17	17	601	116.5	MS2	58W	635914
F	120/70 ZR 17	17	601	116.5	MS3	58W	635915
R	180/60 ZR 17	17	649	182.5	MS0	75W	634978
R	180/60 ZR 17	17	649	182.5	MS2	75W	634979
R	180/60 ZR 17	17	649	182.5	MS3	75W	634980
R	180/60 ZR 17	17	649	182.5	MS4	75W	634981
R	200/60 ZR 17	17	669	202	MS0	80W	635103
R	200/60 ZR 17	17	669	202	MS2	80W	635104
R	200/60 ZR 17	17	669	202	MS4	80W	635105

* Dunlop recommends that optimum performance will be found with an operating pressure in this range.

** Recommendation for track use only. For use on public roads refer to vehicle owners manual. Use 100°C warmers if available, in which case add 0.1bar to the pressure in the table.

*** For safe operation never run below the minimum pressure.

**** Pressures set in the tyre warmers reduces any chance of errors and are generally more reliable & consistent.

