

METZELER

ROAD RACING and SUPERMOTO RANGE 2021

METZELER MOTORCYCLE TYRES		RIM	WIDTH	DIAMETER	DIAMETER	WEIGHT	COLD PRESSURE	HOT PRESSURE	WARMERS	
		recommended (Inches)	mm (Inches)	centre mm (Inches)	shoulder mm (Inches)	kgs (lbs/pound)	recommended range (w/o warmers) bar (psi)	recommended range (after warmers) bar (psi)	usage °C (°F)	
RACETEC RR SLICK										
DRY SLICK	17"	front 120/70 R17	3.50	120 (4.72)	604 (23.78)	501 (19.72)	4.3 (9.5)	2.1/2.2 (30/32)	2.2/2.5 (32/36)	50 mins. @ 80°C (176°F)
		rear 180/60 R17	5.50	190 (7.48)	656 (25.83)	527 (20.75)	6.5 (14.3)	1.6/1.8 (23/26)	1.7/1.9 (25/28)	
		rear 200/60 R17	6.00	200 (7.87)	662 (26.06)	530 (20.87)	6.7 (14.7)	1.6/1.8 (23/26)	1.7/1.9 (25/28)	
	RACETEC TD SLICK									
	17"	front 120/70 R17	3.50	120 (4.72)	604 (23.78)	501 (19.72)	4.3 (9.5)	2.1/2.2 (30/32)	2.2/2.5 (32/36)	50 mins. @ 80°C (176°F)
		rear 180/55 ZR17	5.50	181 (7.12)	641 (25.23)	529 (20.83)	5.8 (12.8)	1.6/1.8 (23/26)	1.7/1.9 (25/28)	
		rear 180/60 ZR17	5.50	190 (7.48)	656 (25.83)	527 (20.75)	6.5 (14.3)	1.6/1.8 (23/26)	1.7/1.9 (25/28)	
		rear 190/55 ZR17	5.50 - 6.00	191 (7.51)	652 (25.67)	527 (20.75)	6.2 (13.7)	1.6/1.8 (23/26)	1.7/1.9 (25/28)	
		rear 200/55 R17	6.00	193 (7.60)	656 (25.83)	531 (20.90)	6.5 (14.3)	1.6/1.8 (23/26)	1.7/1.9 (25/28)	
	RACETEC SM									
	16.5"	front 125/75 R420	3.50	120 (4.72)	600 (23.62)	489 (19.25)	4.4 (9.7)	1.6/1.8 (23/26)	1.8/1.9 (26/28)	40 mins. @ 80°C (176°F)
	17"	front 125/75 R17	3.50	120 (4.72)	604 (23.77)	499 (19.64)	4.3 (9.5)	1.6/1.8 (23/26)	1.8/1.9 (26/28)	
rear 165/55 R17		5.00 - 5.50	162 (6.38)	631 (24.84)	521 (20.51)	5.4 (11.9)	1.5/1.6 (22/23)	1.6/1.7 (23/25)		
RACETEC SM RAIN										
RAIN	16.5"	front 125/75 R420	3.50	120 (4.72)	600 (23.62)	489 (19.25)	4.4 (9.7)	2.3 (34)	2.4 (35)	30 mins. @ 50°C (122°F)
	17"	front 125/75 R17	3.50	120 (4.72)	604 (23.77)	499 (19.64)	4.3 (9.5)	2.3 (34)	2.4 (35)	
		rear 165/55 R17	5.50	162 (6.38)	631 (24.84)	521 (20.51)	5.6 (12.3)	1.9 (28)	2.0 (29)	
RACETEC RR										
DRY DOT	17"	front 120/70 ZR17	3.50	120 (4.72)	604 (23.78)	501 (19.72)	4.3 (9.5)	2.0/2.2 (29/32)	2.1/2.4 (30/35)	50 mins. @ 80°C (176°F)
		rear 160/60 ZR17	4.50 - 5.00	165 (6.50)	631 (24.84)	521 (20.51)	5.6 (12.4)	1.6/1.8 (23/26)	1.7/1.9 (25/28)	
		rear 180/55 ZR17	5.50	181 (7.12)	641 (25.23)	529 (20.83)	5.8 (12.8)	1.6/1.8 (23/26)	1.7/1.9 (25/28)	
		rear 180/60 ZR17	5.50	190 (7.48)	656 (25.83)	527 (20.75)	6.5 (14.3)	1.6/1.8 (23/26)	1.7/1.9 (25/28)	
		rear 200/55 ZR17	6.00	200 (7.87)	662 (26.06)	530 (20.87)	6.7 (14.7)	1.6/1.8 (23/26)	1.7/1.9 (25/28)	
	18"	front 110/80 ZR18	2.50 - 3.00	114 (4.49)	632 (24.88)	545 (21.45)	4.8 (10.5)	2.0/2.2 (29/32)	2.1/2.4 (30/35)	
		rear 130/80 ZR18	3.00 - 3.50	129 (5.01)	670 (26.38)	577 (22.72)	5.3 (11.7)	1.7/1.9 (25/28)	1.8/2.0 (26/29)	
		rear 150/65 ZR18	4.00 - 4.50	160 (6.29)	648 (25.51)	552 (21.73)	6.5 (14.3)	1.7/1.9 (25/28)	1.8/2.0 (26/29)	
rear 160/60 ZR18	4.25 - 5.00	164 (6.46)	648 (25.51)	554 (21.81)	6.5 (14.3)	1.7/1.9 (25/28)	1.8/2.0 (26/29)			
RACETEC RR INTERMEDIATE										
INTER	17"	front 120/70 R17	3.50	120 (4.72)	604 (23.78)	501 (19.72)	4.2 (9.3)	2.3 (34)	2.4 (35)	30 mins. @ 50°C (122°F)
		rear 190/60 R17	5.50 - 6.00	193 (7.60)	656 (25.83)	531 (20.90)	6.7 (14.8)	1.9 (28)	2.0 (29)	
RACETEC RR RAIN										
RAIN	17"	front 120/70 R17	3.50	120 (4.72)	604 (23.78)	501 (19.72)	4.3 (9.5)	2.3 (34)	2.4 (35)	30 mins. @ 50°C (122°F)
		rear 190/60 R17	5.50 - 6.00	193 (7.60)	656 (25.83)	531 (20.90)	7.1 (15.6)	1.9 (28)	2.0 (29)	